Willow Creek Subbasin Assessment and TMDLs





Department of Environmental Quality

May 18, 2004

Willow Creek Subbasin Assessment and TMDLs

May 18, 2004

Prepared by:
Melissa Thompson
Idaho Falls Regional Office
Department of Environmental Quality
900 North Skyline, Suite B
Idaho Falls, Idaho 83201

Acknowledgments

Rick Passey, Co-Chairman of the Willow Creek Watershed Advisory Group, bestowed considerable knowledge of the watershed and assisted with land access obtainment. Troy Saffle and Thomas Herron, both of the DEQ-Idaho Falls Regional Office, imparted extensive technical and field support, along with editorial reviews. Steve Robinson, Beneficial Use Reconnaissance Program (BURP) coordinator for the DEO-Idaho Falls Regional Office, collected and supplied field data. Mark Shumar of DEQ-Technical Services was a contributing author and provided a great deal of technical assistance. Dan Kotanski and Pat Koelsch, both of the Bureau of Land Management, provided water quality data, PFC, and fisheries information. Christine Fischer with the Idaho Association of Soil Conservation Districts (IASCD) contributed water quality data. Elliot Traher of the National Resource Conservation Service (NRCS) provided land use and restoration project information. Mike Philbin, Lee Leffert, and Jim Capurso with the U.S. Forest Service (USFS) provided water quality, fisheries, and range management data for the subbasin. Heath Hancock of the Idaho Department of Lands (IDL) contributed range management data, PFC, and restoration project information. Jim Fredericks and Bill Schrader of Idaho Fish and Game (IDFG) supplied fish data and restoration project information. Alicia Lane with the Bureau of Reclamation (BOR) provided water quality data and insight pertaining to the Ririe Reservoir dam.

Thank you all for contributing to the Willow Creek Subbasin Assessment and TMDL.

Cover photo provided by Idaho Department of Environmental Quality.

Table of Contents

Acknowledgments	i
Table of Contents	iii
List of Tables	v
List of Figures	ix
List of Appendices	
Abbreviations, Acronyms, and Symbols	
Abbieviations, Actoryms, and Cymbols	
Executive Summary	
Subbasin at a GlanceKey Findings	
Rey Findings	XVIII
Subbasin Assessment – Watershed Characterization	1
1.1 Introduction	
Background	
Idaho's Role	
1.2 Physical and Biological Characteristics	
Climate	
Subbasin Characteristics	7
Sub-watershed Characteristics	28
Stream Characteristics	38
1.3 Cultural Characteristics	40
Land Use	40
Land Ownership, Cultural Features, and Population	42
History and Economics	45
2. Subbasin Assessment – Water Quality Concerns and Status	47
2.1 Water Quality Limited Segments Occurring in the Subbasin	
2.2 Applicable Water Quality Standards	
Beneficial Use Designations	
Water Quality Criteria	
Antidegradation Policy	
2.3 Summary and Analysis of Existing Water Quality Data	
Flow Characteristics	
Water Column Data	
	60

	Status of Beneficial Uses	83
	Conclusions	83
	2.4 Data Gaps	85
3.	Subbasin Assessment – Pollutant Source Inventory	
	3.1 Sources of Pollutants of Concern	
	Point Sources	87
	Nonpoint Sources	87
	Pollutant Transport	88
	Subbasin Assessment – Summary of Past and Present Po	
Ef	fforts	89
5.	Total Maximum Daily Load(s)	93
	5.1 Instream Water Quality Targets	94
	Design Conditions	94
	Target Selection	94
	Monitoring Points	95
	5.2 Load Capacity	
	5.3 Estimates of Existing Pollutant Loads	99
	5.4 Load Allocation	
	Wasteload Allocation	100
	Load Allocation	100
	Margin of Safety	
	Seasonal Variation	
	Background	
	Reserve	
	5.5 Implementation Strategies	
	Approach	
	Time Frame	
	Responsible Parties	
	Monitoring Strategy	
	5.6 Conclusions	111
Re	eferences Cited	113
GI	lossary	119

List of Tables

Table A. Streams and pollutants for which TMDLs were developedxvii
Table B. Summary of assessment outcomesxxiv
Table 1. Weather Stations in the vicinity of the Willow Creek Subbasin4
Table 2. Monthly climate summary for Henry, Idaho5
Table 3. Monthly climate summary for Swan Valley 2E, Idaho5
Table 4. Monthly climate summary for Palisades, Idaho5
Table 5. Monthly climate summary for Idaho Falls 2 ESE, Idaho6
Table 6. Monthly climate summary for Idaho Falls 16SE, Idaho6
Table 7. Mean maximum daily air temperature data for two Agrimet Stations7
Table 8. Snotel (NRCS) Snow Water Content Monitoring sites nearest the Willow Creek Subbasin7
Table 9. USGS Gauging Stations12
Table 10. STATSGO Map Unit Summary15
Table 11. Correlation between STATSGO Map Units and Bonneville County Soil Associations20
Table 12. Correlation between STATSGO Map Units and Bingham Area Soil Associations20
Table 13. Bonneville County Soil Associations – Additional Information24
Table 14. Bingham County Soil Associations – Additional Information25
Table 15. Common and Scientific Names for Vegetation Mentioned in this

Associations
Table 17. Physical attributes of the 5 th field HUCs within the Willow Creek Subbasin
Table 18. Land use in the Willow Creek Subbasin 40
Table 19. Land ownership in the Willow Creek Subbasin 42
Table 20. §303(d) Segments in the Willow Creek Subbasin 47
Table 21. Willow Creek Subbasin designated beneficial uses 52
Table 22. Willow Creek Subbasin existing/presumed beneficial uses 53
Table 23. Monthly flow statistics for Willow Creek USGS gauging stations in HUC #1704020559
Table 24. Peak streamflow (cfs) for station #13057940, Willow Creek below Tex Creek near Ririe, ID (1978-1979, 1986-2001)
Table 25. 2001 IDFG Temperature data and number of days where water temperatures exceeded the cold water aquatic life criteria during the entire monitoring period.
Table 26. 2001 IDFG Temperature data and number of days where water temperatures exceeded the salmonid spawning criteria during the entire monitoring period
Table 27. 2000, 2001, 2002 USFS Temperature data and number of days where water temperatures exceeded the cold water aquatic life criteria during the entire monitoring period
Table 28. 2000, 2001, 2002 USFS Temperature data and number of days where water temperatures exceeded the salmonid spawning criteria during the entire monitoring period
Table 29. 2003 DEQ Temperature data and number of days where water temperatures exceeded the cold water aquatic life criteria during the entire monitoring period

Table 30. 2003 DEQ Temperature data and number of days where water temperatures exceeded the salmonid spawning criteria during the entire	
monitoring period	66
Table 31. BLM water quality monitoring data	67
Table 32. Nutrient data at five BLM sample collection sites	69
Table 33. MSE McNeil Sediment Core sample sites and percentage depth fines.	73
Table 34. DEQ Sediment Core sample locations and percentage depth fines	s.73
Table 35. DEQ Streambank Erosion Inventory Summary	74
Table 36. MSE streambank assessment data summary	75
Table 37. DEQ fish data summary	79
Table 38. BLM fish data summary	81
Table 39. USFS fish data summary	81
Table 40. IDFG fish data summary	82
Table 41. Data gaps in the Willow Creek Subbasin	86
Table 42. Willow Creek Subbasin Conservation Programs	89
Table 43. Sediment load allocations for Willow Creek Subbasin	.100
Table 44. Temperature load allocations for Willow Creek Subbasin	.101
Table 45. Nutrient load allocations for Willow Creek	.102
Table B-1. Stream Characteristics from BURP field data	.147
Table C-1. Metric - English unit conversions	.150
Table E-1. Data sources for Willow Creek Subbasin Assessment	.161

Table F-1.	Meadow Creek water quality data	165
Table F-2.	Tex Creek water quality data	165
Table F-3.	Willow Creek at Kepp's Crossing water quality data	165
Table F-4.	Birch Creek water quality data	166
Table F-5.	Sellars Creek water quality data	166
Table F-6.	Willow Creek at Pole Bridge water quality data	167
Table F-7.	Homer Creek water quality data	167
Table F-8.	Grays Lake Outlet water quality data	167
Table G-1.	DEQ BURP Water Quality Data	171
Table H-2.	Willow Creek McNeil data	175
Table H-3.	Willow Creek McNeil data	176
Table H-4.	Lava Creek McNeil data	176
Table H-5.	Mill Creek McNeil data	177
Table H-6.	Grays Lake Outlet McNeil data	177
Table H-7.	Sellars Creek McNeil data	178
Table H-8.	Willow Creek McNeil data	179
	BLM summary of Willow Creek watershed stream riparian	191
Table J-2.	IDL 1999 PFC data	192
Table J-3.	IDL 2001 PFC data	194
Table I.4	IDL 2002 PEC data	105

List of Figures

	_
Figure A. Willow Creek Subbasin at a Glance	
Figure 1. Willow Creek Subbasin	
Figure 2. Willow Creek Subbasin Geology	.13
Figure 3. Soil Units on Soil Erosion Potential.	
Figure 4. Soil Units on Average Annual precipitation	
Figure 5. Soil Units on Slope	
Figure 6. Soil Units on Landcover.	
Figure 7. General Soils Map – Bonneville County	
Figure 8. General Soils Map – Bingham County	
Figure 9. Willow Creek Subbasin 5 th Field Watersheds	
Figure 10. Transport Coefficient in Willow Creek Subbasin	
Figure 11. Sediment Sources in the Willow Creek Subbasin	
Figure 12. Natural Sensitivity in the Willow Creek Subbasin	
Figure 13. Geomorphic Risk in the Willow Creek Subbasin	
Figure 14. Willow Creek Subbasin Waterbodies	
Figure 15. Land Use in the Willow Creek Subbasin	
Figure 16. Major Cultural Features of the Willow Creek Subbasin	.43
Figure 17. Land Ownership in the Willow Creek Subbasin	.44
Figure 18. 303(d) listed streams in the Willow Creek Subbasin	.50
Figure 19. Annual mean flow (cfs) for station #13057940, Willow Creek below	N
Tex Creek near Ririe, ID (1978 and 1986-2000)	.57
Figure 20. Annual mean flow (cfs) for station #13058000, Willow Creek near	
Ririe, Id (1917-1919, 1963-1978, and 1986-2000)	
Figure 21. Monthly flow statistics for station #13057940, Willow Creek below	
Tex Creek near Ririe, ID (1977-1979, 1985-2001)	.59
Figure 22. Monthly flow statistics for station #13058000, Willow Creek near	
Ririe, ID (1903-1904, 1917-1928, and 1962-2001)	.60
Figure 23. Peak streamflow (cfs) for station # 13058000, Willow Creek near	
Ririe, ID (1903-2001)	.61
Figure 24. Total discharge from gauge stations at Grays Lake, Outlet	
(13057500) and Diversion (13057500) for the months of April-Sept. 2002.	62
Figure 25. Willow Creek Subbasin BURP Monitoring Sites	.71
Figure 26. MSE Streambank Erosion Inventory and McNeil Sediment Sample	,
Sites	
Figure 27. NRCS Conservation Projects in the Willow Creek Subbasin	.90
Figure 28. Total Phosphorus Load Capacity for Willow Creek	.98
Figure A-1. Snotel Graph for Pine Creek Pass, ID1	
Figure A-2. Snotel Graph for Sedgewick Peak, ID1	
Figure A-3. Snotel Graph for Slug Creek Divide, ID1	
Figure A-4. Snotel Graph for Somsen Ranch, ID1	

List of Appendices

Appendix A.	SNOTEL Snow Water Content Graphs1	39
Appendix B.	Stream Characteristics from BURP field data1	45
Appendix C.	Unit Conversion Chart1	49
Appendix D.	State and Site-Specific Standards and Criteria1	51
Appendix E.	Data Sources1	59
Appendix F.	IASCD Water Quality Data1	63
Appendix G.	DEQ BURP Water Quality Data1	69
Appendix H.	Subsurface Fine Sampling Results1	73
Appendix I.	Streambank Erosion Inventory Method1	81
Appendix J.	Proper Functioning Condition Data1	89
Appendix K.	Stream Macroivertebrate Index1	97
Appendix L.	Distribution List2	201
Appendix M.	Public Comments2	205

Abbreviations, Acronyms, and Symbols

§303(d)	Refers to section 303	DEQ	Department of Environmental Quality
	subsection (d) of the Clean Water Act, or a list of impaired waterbodies	DO	dissolved oxygen
	required by this section	DWS	domestic water supply
μ	micro, one-one thousandth	EPA	United States Environmental Protection Agency
§	Section (usually a section of federal or state rules or statutes)	F	Fahrenheit
ADB	assessment database	GIS	Geographical Information Systems
AWS	agricultural water supply	HUC	Hydrologic Unit Code
BLM	United States Bureau of Land Management	I.C.	Idaho Code
ВМР	best management practice	IDAPA	Refers to citations of Idaho administrative rules
BOD	biochemical oxygen demand	IDFG	Idaho Department of Fish and Game
BOR	United States Bureau of Reclamation	IDL	Idaho Department of Lands
BURP	Beneficial Use Reconnaissance Program	km	kilometer
C	Celsius	km ²	square kilometer
CFR	Code of Federal Regulations	LA	load allocation
CFK	(refers to citations in the federal administrative rules)	LC	load capacity
cfs	cubic feet per second	m	meter
cm	centimeters	m^3	cubic meter
		mi	mile
CWA	Clean Water Act	mi ²	square miles
CWAL	cold water aquatic life	MBI	macroinvertebrate index

mg/L	milligrams per liter	STATSG		State Soil Geographic Database
mm	millimeter	TDS		l dissolved solids
MOS	margin of safety			
n.a.	not applicable	TKN	tota	l Kjeldahl nitrogen
NA	not assessed	TMDL	tota	l maximum daily load
NB	natural background	TP	tota	l phosphorus
nd	-	TS	tota	l solids
	no data (data not available)	TSS	tota	l suspended sediment
NFS	not fully supporting	t/y	tons	s per year
NPDES	National Pollutant Discharge Elimination System	U.S.	Uni	ted States
NRCS	Natural Resources Conservation Service	U.S.C.	Uni	ted States Code
PCR	primary contact recreation	USDA		ted States Department of iculture
PFC	proper functioning condition	USFS	Uni	ted States Forest Service
ppm	part(s) per million	USGS	Uni	ted States Geological Survey
QA	quality assurance	WAG	Wa	tershed Advisory Group
QC	quality control	WBAG	Wai	terbody Assessment Guidance
SBA	subbasin assessment	WBID	wat	erbody identification number
SCR	secondary contact recreation	WLA	was	teload allocation
SFI	DEQ's stream fish index	WQLS	wat	er quality limited segment
SHI	DEQ's stream habitat index	wqs	wat	er quality standard
SMI	DEQ's stream macroinvertebrate index			
SS	suspended sediment			

Executive Summary

The federal Clean Water Act (CWA) requires that states and tribes restore and maintain the chemical, physical, and biological integrity of the nation's waters. States and tribes, pursuant to Section 303 of the CWA, are to adopt water quality standards necessary to protect fish, shellfish, and wildlife while providing for recreation in and on the waters whenever possible. Section 303(d) of the CWA establishes requirements for states and tribes to identify and prioritize waterbodies that are water quality limited (i.e., waterbodies that do not meet water quality standards). States and tribes must periodically publish a priority list of impaired waters, currently every two years. For waters identified on this list, states and tribes must develop a total maximum daily load (TMDL) for the pollutants, set at a level to achieve water quality standards. This document addresses the waterbodies in the Willow Creek subbasin that have been placed on what is known as the "§303(d) list."

This subbasin assessment and TMDL analysis has been developed to comply with Idaho's TMDL schedule. This assessment describes the physical, biological, and cultural setting; water quality status; pollutant sources; and recent pollution control actions in the Willow Creek Subbasin located in southeast Idaho. The first part of this document, the subbasin assessment, is an important first step in leading to the TMDL. The starting point for this assessment was Idaho's current §303(d) list of water quality limited waterbodies. Twenty segments of the Willow Creek Subbasin were listed on this list. The subbasin assessment portion of this document examines the current status of §303(d) listed waters and defines the extent of impairment and causes of water quality limitation throughout the subbasin. The loading analysis quantifies pollutant sources and allocates responsibility for load reductions needed to return listed waters to a condition of meeting water quality standards.

Subbasin at a Glance

The Willow Creek Subbasin in southeastern Idaho (Figure A) is a watershed of the Upper Snake River Basin. Waters of Willow Creek are connected to the Snake River through a complex irrigation system located below the Ririe Reservoir.

Native fish populations, water quality, and riparian habitat conditions are issues of concern in the subbasin. The cumulative effects of land management in riparian areas, human-caused stream alterations, roads, limited recreation, and pockets of timber harvesting have combined to limit compliance with water quality standards. The production and survival of resident fishes is also impacted throughout the watershed.

Rainbow trout, Yellowstone cutthroat trout, brook trout, and brown trout have all been documented in the watershed. Yellowstone cutthroat trout is a state sensitive species carefully managed by the Idaho Department of Fish and Game (IDFG). Fish count data show that salmonid populations, a family to which the fish listed belong, are trending downwards in the subbasin.

Designated uses for Willow Creek (proper) are: cold water aquatic life, salmonid spawning, primary contact recreation, secondary contact recreation, domestic water supply, and special

resource water. Undesignated uses are cold water aquatic life and primary and secondary contact recreation for the remainder of the watershed, which includes the following: Birch Creek, Sellars Creek, Mill Creek, Crane Creek, Long Valley Creek, Grays Lake Outlet, Homer Creek, Brockman Creek, Corral Creek, Sawmill Creek, Lava Creek, Hell Creek, Tex Creek, and Meadow Creek.




Figure A. Willow Creek Subbasin at a Glance

Biological assessments conducted by the Idaho Department of Environmental Quality (DEQ) in discrete locations have shown that several streams in the subbasin are water quality limited. Sediment and temperature are the primary pollutants of concern with some nutrient listings. Flow alteration has also been identified as a source of perturbation in the subbasin.

Data has been collected and analyzed to evaluate the scope of the water quality limiting issues on the 303(d) listed streams in the Willow Creek Subbasin. Fourteen sediment, twelve temperature, and one nutrient TMDLs, as summarized in Table A, have been developed from the results of the data, or in response to the data.

Table A. Streams and pollutants for which TMDLs were developed.

Stream	Pollutant(s)
Brockman Creek	Sediment, Temperature
Buck Creek	Sediment
Corral Creek	Sediment, Temperature
Crane Creek	Sediment
Grays Lake Outlet	Temperature
Hell Creek	Sediment, Temperature
Homer Creek	Sediment, Temperature
Lava Creek	Sediment, Temperature
Meadow Creek	Sediment
Mill Creek	Sediment, Temperature
Rock Creek	Temperature
Sawmill Creek	Sediment, Temperature
Sellars Creek	Sediment, Temperature
Seventy Creek	Sediment
Tex Creek	Sediment, Temperature
Willow Creek	Sediment, Temperature, Nutrients

TMDLs for sediment are quantified through streambank erosion inventories and road sediment modeling. Sediment loading targets were developed based on literature detailing expected natural conditions and substrate sediment impacts on salmonid spawning. The target values established will be used to quantify streambank recovery and determine the need for additional management practices to improve water quality.

TDML targets for substrate sediment are adopted from literature detailing its impact on salmonid egg and fry emergence. The target values established in this assessment will be used to indicate trends related to channel morphology and streambank recovery. Beneficial use support status and compliance with state water quality standards will be used to determine the need for additional best management practices to improve water quality.

Temperature TMDLs have been developed for all streams, where thermograph data has been collected, to support salmonid spawning and cold water aquatic life. Salmonid spawning has been determined to be the presumed use for all streams in the subbasin.

Reduced riparian vegetation contributes to accelerated streambank erosion which results in increased thermal loading which, combined with associated changes in channel morphology are the primary causes of increased temperature loading in affected streams.

Elevated temperatures from reduced riparian vegetation and accelerated streambank erosion have been exacerbated by an ongoing drought in the subbasin.

TDMLs were not developed for streams listed as flow altered. Streams listed as flow altered and streams discovered to be flow altered for significant portions of the year do not have a reasonable potential to support beneficial uses. The EPA does not believe that flow (or lack of flow) is a pollutant as defined by CWA Section 502(6). Since TMDLs are not required to be established for waterbodies impaired by pollution but not pollutants, TMDLs will not be developed for flow altered streams, at this time. They will be relisted as flow altered.

Key Findings

Land use and management, along with stream conditions throughout the entire subbasin, are primarily homogeneous. The magnitude of sediment loading within the subbasin is widespread, predominantly attributable to streambank erosion from over-utilization of riparian habitat. Some additional sources of sediment loading are poor road maintenance, road crossings, and limited mass wasting (downward movement of earth and rock due to the force of gravity.)

Anthropogenic (human-related) causes of flow alteration in the subbasin include diversion for stock watering and irrigation. It is not likely that beneficial uses will be restored in streams of the watershed where dewatering from surface water diversion occurs during significant portions of the year. The potential exists for a voluntary and cooperative management agreement to improve flow conditions without negatively impacting the rural economy.

DEQ has developed recommendations for the reduction of sediment from streambank erosion and road erosion within the Willow Creek Subbasin. The recommendations result in beneficial use support through improving streambank stability and reducing road erosion, ultimately improving riparian vegetation. All sediment loads are developed through the estimation of sediment delivery to streams from streambank and road erosion.

TDMLs are recommended for sediment, temperature, and nutrients based upon the following criteria:

Sediment TMDLs are based on literature suggesting that 80% bank stabilities show for full beneficial use support. Cold water aquatic life and salmonid spawning are expected to be fully supported at 80% streambank stability. Instream sediment targets have been identified from literature values that are supportive of salmonid spawning and coldwater aquatic life. These target values are set at 28% fine sediment less than 6.35 mm in diameter in spawning habitat and will be used to track the progress of streambank stabilization and the reduction of depth fines to determine the need for additional management practices to improve water quality in the Willow Creek Subbasin.

Temperature TMDLs have been developed for streams where temperature data has been collected and shows an exceedance of temperature criteria in greater than 10% of observation

days during spring or fall spawning periods. Thermograph data established that temperature TMDLs were necessary to meet the numeric salmonid spawning criteria [IDAPA 58.01.02.250(02)]. All Temperature TMDL load reductions were developed by quantifying the daily temperature exceedance during spring and fall spawning and subtracting that from the spawning temperature criteria to formulate the load reduction (allocation). Streambank erosion, reduced riparian vegetation, and low flow conditions are the causes of increased water temperatures in the subbasin. The TMDL temperature targets are the salmonid spawning temperature criteria established in Idaho's administrative code [IDAPA 58.01.02.250(02)].

Nutrient TMDLs have been established for Willow Creek where nutrient monitoring data shows elevated levels of phosphorus and nitrogen in conjunction with low dissolved oxygen levels in the stream and visual observation of deleterious levels of aquatic plant growth. The TMDL target values are based on EPA suggestions for the preservation of cold water aquatic life.

There are twenty-two 303(d) listed stream segments in the Willow Creek Subbasin. In the text that follows there are descriptions of the water quality issues related to the 303(d) listed streams. Table B provides a summary of the assessment outcomes for each of the 303(d) listed stream segments.

Birch Creek

Birch Creek's water is retained upstream in two locations, thus reducing flow below Bone Road to less than 1 cfs a large portion of the year. Flow alteration is the driving issue here so, a sediment TMDL will not be developed for Birch Creek.

Brockman Creek

Predominant landuse activities on Brockman Creek are sheep and cattle grazing. The over utilization of riparian zones has contributed to active downcutting, creating a stream that is highly entrenched with high width/depth ratios and lateral recession rates. The estimated current sediment-loading rate is 384 tons/mile/year. To address sediment issues, a TMDL was developed prescribing an annual loading rate of 25 tons/mile/year, provided banks are restored to 80% stability.

Brockman Creek is not listed for temperature, but thermograph data show that stream temperatures exceed Idaho's salmonid spawning criteria. In order to protect beneficial use support, TMDLs were developed for Brockman Creek. Brockman Creek's current temperature-loading rate is 19.7°C (maximum daily) and 17.84°C (maximum daily average). A 34% reduction in the maximum daily temperature is necessary to meet the criteria.

Corral Creek

Corral Creek is listed for sediment and temperature. Land use is predominated by sheep and cattle grazing where riparian impacts are evident with high bank instabilities. The current

estimated erosion rate is 226 tons/mile/year. The TMDL prescribes a sediment-loading rate of 18 tons/mile/year.

Temperature exceedances were also documented on Corral Creek, with a current maximum daily temperature load of 22.39°C. The temperature TMDL prescribes a 42% reduction in the maximum daily average temperatures.

Crane Creek

Crane Creek is 303(d) listed for sediment from source to mouth. Grazing is the predominant source of sedimentation in the drainage, with limited riparian road impacts. Bank stabilities of 67% and 66% were documented on Crane Creek. The current estimated erosion rate is 172 tons/mile/year. The TMDL prescribes a sediment-loading rate of 25 tons/mile/year.

Grays Lake Outlet

Sediment, nutrients, and temperature are 303(d) listed pollutants above the falls on Grays Lake Outlet. The water from Grays Lake is allocated for irrigation, hence discharge to Grays Lake Outlet is limited above the falls. Temperature, nutrient and sediment TMDLs will not be developed for the upper section of Grays Lake Outlet because flow alteration is the overriding issue is this particular stream segment. Grays Lake Outlet, above the falls, should be delisted for sediment and nutrients and relisted as flow altered.

Channel recharge restores streamflow to Grays Lake Outlet below the falls, and Grays Lake Outlet is temperature listed from headwaters to mouth and temperature exceedances were documented in two locations. Current temperature loading is 28.34°C (maximum daily) and 21.58°C (maximum daily average). The TMDL prescribes a 54% and 58% reduction in maximum and average daily stream temperatures. Because Grays Lake Outlet is flow limited above the falls, the temperature TMDL applies to waters below the falls.

Hell Creek

Hell Creek is listed for sediment and nutrients. Land use is predominated by cattle grazing, and streambank stabilities less than the 80% stability target were observed. The current estimated sediment-loading rate on Hell Creek is 402 tons/mile/yr. The TMDL prescribes a sediment-loading rate of 39 tons/mile/year.

Hell Creek is not 303(d) listed for temperature, but stream temperature exceedances were documented. Current temperature loading is 19.51°C (maximum daily) and 17.41°C (maximum daily average). The TMDL prescribes 33% and 48% reductions in maximum and average daily temperatures.

Homer Creek

Homer Creek is 303(d) listed for sediment and Homer Creek's sediment sources are related to grazing. Streambank conditions that are below the DEQ 80% stability target were

observed. The current estimated erosion rate is 411 tons/mile/year, and the TMDL prescribes an erosion rate of 20 tons/mile/year.

Homer Creek is not 303(d) listed for temperature, but stream temperature exceedances were documented. Current temperature loading is 26.42°C (maximum daily) and 18.79°C (maximum daily average). The temperature TMDL prescribes 51% and 52% load reductions in the maximum and average daily temperatures.

Lava Creek

Lava Creek is 303(d) listed for sediment and temperature. Stream temperature data reveal current temperature loads of 22.80°C (maximum daily) and 18.44°C (maximum daily average). The TMDL prescribes a 43% and 51% reduction in maximum and average daily temperatures. It is expected that stream temperatures will improve with riparian zone enhancement.

A culvert on upper Lava Creek continuously exists in a state that inhibits downstream flow. It is speculated that beaver activity, combined with anthropogenic actions, continue to create this condition. It is likely that eliminating the anthropogenic cause of this condition and clearing the obstruction will assist in improving stream temperatures.

Streambank erosion inventories show bank stabilities of 26% at the upper inventory site and 55% at the lower inventory site. The current sediment-loading rate is 537 tons/mile/year. The TMDL prescribes a sediment-loading rate of 16 tons/mile/year.

Long Valley Creek

Listed for sediment and temperature, Long Valley Creek parallels the Long Valley Road. Land use on Long Valley Creek consists of grazing and hay production and bank stabilities were observed below the 80% stability target. An earthen dam retains water in the Robinson Reservoir to impound spring runoff waters for irrigation. Because flow alteration is the prevailing issue, TMDLs will not be developed for Long Valley Creek. Long Valley Creek should be delisted for sediment and temperature and relisted as flow altered.

Meadow Creek

Meadow Creek is listed for sediment, and the principal sources of sediment are streambank erosion in the upper reaches and road erosion in the lower sections. The sediment load allocations have been developed via erosion inventories and road erosion modeling. From headwaters to South Fork Meadow Creek, streambank stabilities of 80% have been achieved from cessation and/or rotation of grazing practices in the vicinity. The current estimated erosion rate from road and streambank erosion is 60 tons/mile/year. A sediment-loading rate of 34 tons/mi/year, from bank erosion, is anticipated if all streambanks are restored to 80% stability. A 50% reduction in road erosion should occur for beneficial use support, prescribing a road sediment-loading rate of 6 tons/mile/year.

Mill Creek

The land surrounding Mill Creek is private and state owned with grazing the principal land use. Monitoring and observations show the largest impacts on the creek are in the middle and lower reaches where land utilization is maximized. Riparian fencing below the headwaters has contributed to riparian improvement, thereby reducing streambank erosion. Substrate samples collected on Mill Creek, above the Willow Creek confluence, had 51% of the sediment fines less than 6.35 mm. Streambank erosion inventories showed the highest concentration of sedimentation occurring in the middle reaches of Mill Creek, above the Blackfoot Reservoir Road crossing. The current estimated erosion rate from streambank erosion is 26 tons/mile/year. The TMDL prescribes a loading rate of 8 tons/mile/year.

Stream temperature exceedances were documented with current temperature loading at 24°C (maximum daily) and 18.2°C (maximum daily average). The TMDL prescribes a 46% and 51% reduction in maximum and average daily temperatures.

Buck Creek is a tributary of Mill Creek and it is located in the Mill Creek assessment unit therefore, Mill Creek load allocations apply to Buck Creek.

Sawmill Creek

Sawmill Creek is 303(d) listed for temperature and sediment. Stream temperature data documented major exceedances in salmonid spawning criteria at 20.9°C (maximum daily) and 18.11°C (maximum daily average). The TMDL prescribes 38% and 50% reductions in maximum and average daily temperatures. The current estimated streambank erosion rate on Sawmill Creek is 340 tons/mile/year. It is expected that a rate of 19 tons/mile/year will occur if banks are restored to 80% stable.

Sellars Creek

Sellars Creek is 303(d) listed for sediment and temperature. Riparian road impacts, riparian grazing, and flow alteration are the three principal causes of perturbation on Sellars Creek. Subsurface fines are higher than the target level of 28% and bank erosivities are highest above the Long Valley Road crossing. Streambank erosion on lower Sellars Creek, below Long Valley Road crossing, is nominal due to limited grazing. The current estimated erosion rate is 304 tons/mile/year. The TMDL prescribes an erosion rate of 11 tons/mile/year.

Stream temperatures in Sellars Creek were above the spawning criteria 65% and 85% of the time. Temperature data show that current temperature loads are 26.7°C (maximum daily) and 18.51°C (maximum daily average). The TMDL prescribes a 51% reduction in both maximum and average daily temperatures.

Seventy Creek

Seventy Creek is 303(d) listed for temperature, sediment, and flow alteration. At this time, data is not available to verify that Seventy Creek is temperature impaired. It is inferred that

temperature impairment from sedimentation will improve, as much as possible in light of flow alterations, with reduced sedimentation and riparian zone improvement. Streambank erosion inventories show banks on Seventy Creek, above the Blackfoot Reservoir Road, to be relatively stable. In the lower reaches, bank stabilities are as low as 39%. Bank erosion on Seventy Creek should not exceed 11 tons/mile/year. The current estimated sediment-loading rate is 288 tons/mile/year.

Tex Creek

Tex Creek is not listed for temperature, but stream temperature data show that there were elevated spawning temperatures at 24.19°C (maximum daily) and 17.96°C (maximum daily average). The TMDL calls for a 46% and 50% reduction in maximum and average daily temperatures.

Sediment impacts on Tex Creek have not been quantified via subsurface sediment sampling because extremely dry conditions over recent years have prohibited the accurate identification of viable spawning habitat. However, it is well documented that the Tex Creek fishery is declining, most likely from stream sedimentation. Based on historic knowledge and fish data spanning several decades, a sediment TMDL is necessary for Tex Creek. Road impacts are the primary source of sedimentation in Tex Creek, so the TMDL is based on road erosion. The current estimated sediment-loading rate is 8 tons/mile/year. The TMDL prescribes a loading rate of 4 tons/mile/year hence, a 50% reduction in road erosion is recommended.

Willow Creek

The entire Willow Creek is 303(d) listed for temperature above and below the reservoir. Temperature logger data show that stream temperatures at Kepp's Crossing are above the salmonid spawning criteria. Documented maximum daily temperatures are 24.54°C during spring spawning and 18.72°C during fall spawning. The TMDL prescribes 47% and 60% reductions in maximum and average daily temperature loads.

Willow Creek, below the reservoir dam to Eagle Rock Canal, is listed for temperature and sediment. Flow from the Ririe Reservoir dam is reduced to no discharge for four to five months of the year. Flow is the limiting factor for beneficial use support below the Ririe Reservoir, so it should be delisted for sediment and temperature and relisted as flow altered.

Willow Creek, from headwaters to Sellars Creek and then from Grays Lake Outlet to the Reservoir, is listed for sediment and temperature. Streambed sampling shows that sediment impacts are evident in spawning gravels at Grays Lake Outlet and Kepp's Crossing. In both instances, subsurface fines were greater than 28%, at 31%. Streambank stabilities are less than 80% in most areas above the Grays Lake Outlet confluence. Bank stabilities meet the 80% target in the steep walled canyons below the confluence with Grays Lake Outlet. The current sediment-loading rate on Willow Creek is 213 tons/mile/year. The TMDL prescribes a sediment-loading rate of 14 tons/mile/year.

High nutrient concentrations in the water column along with nuisance levels of aquatic plant growth were detected in Willow Creek. To address the excess nutrients in Willow Creek, phosphorus and nitrogen load allocations were developed. The load allocations prescribe a 23% reduction in total phosphorus loading and a 73% reduction in nitrogen loading to Willow Creek.

The Ririe Reservoir is 303(d) listed for sediment. Aquatic conditions in the reservoir environment differ from that of streams. Current biological indices for cold water aquatic life apply to streams, not reservoirs. Given this, the Ririe Reservoir listing for sediment should be delisted, because there is insufficient data to compile an accurate assessment. Even though a TMDL will not be developed for the Reservoir, it should be noted that load reductions for upstream Willow Creek and its tributaries should result in an overall net reduction of sediment loading to the Reservoir.

Rock Creek, a tributary of Willow Creek, is 303(d) listed for temperature. Temperature data for Rock Creek itself does not exist however, temperature data is available just downstream of Rock Creek, on Willow Creek (Kepp's Crossing). For the purpose of this TMDL, and the assessment unit reporting system, Rock Creek will receive the same load allocation as Willow Creek proper.

The sediment load that can be assimilated by the streams in the Willow Creek Subbasin, and still meet Idaho's water quality narrative standard for sediment, is unknown. The loading capacity lies somewhere between the current loading level and sediment loads from natural streambank erosion. It is assumed that cold water aquatic life and salmonid spawning would be fully supported at natural background sediment loading rates.

Table B. Summary of assessment outcomes.

Waterbody Segment	Assessment Unit(s) of ID17040205	Pollutant	TMDL(s) Completed	Recommended Changes to §303(d) List	Justification
Birch Creek (WQLS 2042) Headwaters to Willow Creek	SK006_02 SK006_03	Sediment	No	Delist for sediment and relist as flow altered	Flow Altered (Anthropogenic)
Brockman Creek	01/004 00	Nutrient	No	Delist	No Exceedances Documented
(WQLS 2047)	SK024_02 SK024_03 SK025_02	Sediment	Yes	None	TMDL completed
Headwaters to Grays Lake Outlet		Temperature	Yes	None	Exceedances Documented
					TMDL Completed
Buck Creek (WQLS 5232)	SK012 02	Sediment	Yes	None	TMDI completed
Headwaters to Mill Creek	SK012_02	Seuiment	1 68	None	TMDL completed
Corral Creek (WQLS 2048)	SK026_02	Sediment	Yes	None	TMDL completed

Headwaters to Brockman Creek

Waterbody Segment	Assessment Unit(s) of ID17040205	Pollutant	TMDL(s) Completed	Recommended Changes to §303(d) List	Justification
		Temperature	Yes	None	Exceedances Documented
					TMDL completed
Crane Creek (WQLS 2056) Headwaters to Willow Creek	SK014_02	Sediment	Yes	None	TMDL completed
Grays Lake Outlet (WQLS 2044) Grays Lake to Above Falls	SK020_02	Nutrient	No	Delist for nutrient and relist as flow altered	Flow Altered (Anthropogenic)
		Sediment	No	Delist for sediment and relist as flow altered	Flow Altered (Anthropogenic)
Grays Lake Outlet (WQLS 2044) Grays Lake to Willow Creek	SK016_04 SK017_04 Sk019_04	Temperature	Yes	None	Exceedances Documented TMDL completed
Hell Creek	SK029_02 SK029_03	Nutrient	No	Delist	No Exceedances Documented
(WQLS 2045)		Sediment	Yes	None	TMDL completed
Headwaters to Grays Lake Outlet		Temperature	Yes	None	Exceedances Documented
					TMDL completed
Homer Creek		Sediment	Yes	None	TMDL completed
(WQLS 2050) Headwaters to	SK018_02 SK018_03	Temperature	Yes	None	Exceedances Documented
Grays Lake Outlet					TMDL completed
Lava Creek		Sediment	Yes	None	TMDL completed
(WQLS 2046) Headwaters to	SK028_02 SK028_03	Temperature	Yes	None	Exceedances Documented
Grays Lake Outlet					TMDL completed
Long Valley Creek (WQLS 2053) Headwaters to Willow Creek	SK015_02	Sediment	No	Delist for sediment and relist as flow altered	Flow Altered (Natural and Anthropogenic)
		Temperature	No	Delist for temperature and relist as flow altered	Flow Altered (Natural and Anthropogenic)
Meadow Creek (WQLS 2040) Headwaters to Ririe Reservoir	SK032_02 SK032_03	Sediment	Yes	None	TMDL Completed
		Temperature	Yes	None	Exceedances Documented
					TMDL completed

Waterbody Segment	Assessment Unit(s) of ID17040205	Pollutant	TMDL(s) Completed	Recommended Changes to §303(d) List	Justification
Mill Creek	SK012_02 SK012_03	Sediment	Yes	None	TMDL completed
(WQLS 2054) Headwaters to Willow Creek		Temperature	Yes	None	Exceedances Documented TMDL completed
Ririe Lake (WQLS 2036)	SK002_05	Sediment	No	Delist	Not assessed
Rock Creek (WQLS 2028) Headwaters to Willow Creek	SK005_02	Temperature	Yes	None	Exceedances Documented TMDL completed
Sawmill Creek		Sediment	Yes	None	TMDL completed
(WQLS 2049) Headwaters to Brockman Creek	SK027_02	Temperature	Yes	None	Exceedances Documented TMDL completed
Sellars Creek	SK010_02 SK010_03	Flow Alteration	No	None	EPA Policy
(WQLS 2051)		Sediment	Yes	None	TMDL completed
S FK Sellars to Willow Creek		Temperature	Yes	None	Exceedances Documented
Seventy Creek (WQLS 2057) Headwaters to Willow Creek	SK011_02	Flow Alteration	No	None	TMDL completed EPA Policy
		Sediment	Yes	None	TMDL completed
		Temperature	No		Insufficient Data
Tex Creek	(WQLS 2041) SK031_02	Sediment	Yes	None	TMDL completed
Headwaters to		Temperature	Yes	None	Exceedances Documented TMDL completed
Willow Creek (WQLS 2035) Ririe Dam to HUC boundary	SK001_05	Sediment	No	Delist for sediment and relist as flow altered	Flow Altered (Anthropogenic)
		Temperature	No	Delist for temperature and relist as flow altered	Flow Altered (Anthropogenic)
Willow Creek (WQLS 2037) Grays Lake Outlet to Ririe Reservoir	SK004_05 SK005_05	Sediment	Yes	None	TMDL completed
		Temperature	Yes	None	Exceedances Documented
		Nutrients	Yes	None	Exceedances Documented

Waterbody Segment	Assessment Unit(s) of ID17040205	Pollutant	TMDL(s) Completed	Recommended Changes to §303(d) List	Justification
Willow Creek (WQLS 2038)	SK008_04 SK005_04	Nutrients	Yes	None	Exceedances Documented
Sellars Creek to Grays Lake Outlet					
Willow Creek (WQLS 2039) Headwaters to Sellars Creek	SK011_04 SK013_03	Sediment	Yes	None	TMDL completed
		Temperature	Yes	None	Exceedances Documented
		Nutrients	Yes	None	Exceedances Documented